



The **K Series** are security control panels for building protection; hybrid system (wired and wireless input); EN 50131, Grade 2, Class 2 approved. The control panel is equipped of 4/8 zones, expandable to 16/64. It is possible to obtain more zones by double and triple EOL split line (K4-K8). K Series are able to notify one or more situations of ALARM, ROBBERY, TAMPERING and TROUBLE with different carriers:

- **PSTN LINE on board** (voice call, Contact ID, SIA fsk, etc.)
- **GPRS/3G module** (voice call, SMS, Contact ID, DC09 IP protocol for Contact ID and SIA IP)
- IP module (DC09 IP protocol for Contact ID and SIA IP)

The panel can be controlled by new App AMC MANAGER (iOS / Android) with IP module and/or GPRS / 3G module. The programming can be made with keypad and/or PC software. The programming with software can be made remotely with IP module and/or GPRS / 3G module.



Technical Features			
	К 4	К8	K 8 PLUS
ZONES	4 - 16 wired, split double, triple EOL	8 - 32 wired, split double, triple EOL	8 - 64 wired, double, triple EOL
WIRELESS ZONES	64 zones	64 zones	64 zones
OUTPUTS	2 on board - expandable to 8 (with expansions and keypads)	2 on board - expandable to 8 (with expansions and keypads)	2 on board - expandable to 17 (with expansions and keypads)
USER CODE / TAG / REMOTE	32 users	32 users	64 users
AREAS	4	4	8
GROUPS	4	4	4
KEYPAD	4	4	8
TAG READER	4	4	8
LOG EVENTS	1000	1000	1000
PHONE NUMBERS	8 for SMS and private calls + 8 for CMS	8 for SMS and private calls + 8 for CMS	8 for SMS and private calls + 8 for CMS
CARRIERS	PSTN on board, GPRS/3G module, IP module	PSTN on board, GPRS/3G module, IP module	PSTN on board, GPRS/3G module, IP module
REMOTE MANAGEMENT IP - GPRS/3G	by app (iOS - Android)	by app (iOS - Android)	by app (iOS - Android)
REMOTE PROGRAMMING IP - GPRS/3G	by PC software	by PC software	by PC software
TIMERS	4 per day week	4 per day week	4 per day week